## NSN 5935-01-349-5454

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-5454 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape, angle **Overall Length:** 2.090 inches **Overall Height:** 0.615 inches **Overall Width:** 1.000 inches **Distance Between Mounting Facility Centers:** 1.850 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Post jacksocket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 105.0 degrees celsius

Between -55.0 degrees celsius and 105.0 degrees celsius

Thready Qty Per Inch (tpi):

40

Thread Size:
0.112 inches

Terminal Location:
Side single mating end single contact grouping

Contact Material:
Copper alloy single mating end single contact grouping

Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping

## NSN 5935-01-349-5454

**Insert Material:** 

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Plastic polyester glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Tin
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):