NSN 5935-01-349-5637



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-349-5637 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, flange mount external coupling **Overall Length:** Between 1.297 inches and 1.317 inches **Overall Height:** Between 1.024 inches and 1.044 inches **Overall Width:** Between 1.024 inches and 1.044 inches **Environmental Protection:** Heat resistant and cold resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 12-oct single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 95.0 and 141.0 and 208.0 and 236.0 Shell Type: Solid

Connector Locking Method:

Externally threaded shell

Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Thready Qty Per Inch (tpi):

28

Thread Size:

0.625 inches

NSN 5935-01-349-5637

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Resin silicone single mating end
Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0