

View Online at <https://aerobasegroup.com/nsn/5935-01-349-5638>

Body Style:

Right angle type

Overall Length:

6.540 inches

Overall Width:

Between 0.310 inches and 0.330 inches

Body Height:

Between 0.140 inches and 0.160 inches

Environmental Protection:

Corrosion resistant and shock resistant and vibration resistant and humidity resistant and thermal shock resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-c-533, half hard federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response single mating end

Included Contact Quantity:

65 single mating end single contact grouping

Included Contact Type:

Square socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.065 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.