## NSN 5935-01-349-7725

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-7725

Body Style:
Straight shape
Overall Length:
1.596 inches
Overall Height:
0.475 inches
Overall Width:
0.124 inches
Environmental Protection:
Vibration resistant and shock resistant and humidity resistant and salt water resistant and thermal shock resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Polarization Method:
Contact
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping
Insert Material:
Plastic phenolic single mating end and glass fiber single mating end or plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 1
federal specification 2nd treatment response single mating end 1st contact grouping
Terminal Type:
Printed circuit single mating end 1st contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end 1st contact grouping
Insert Material Specification:

mating end or mil-m-14 military specification 3rd material response single mating end

Mil-p-46174 military specification 1st material response single mating end and mil-p-46174 military specification 2nd material response single

#### **Included Contact Quantity:**

15 single mating end 1st contact grouping

### **Included Contact Type:**

Round socket single mating end 1st contact grouping

# NSN 5935-01-349-7725

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.