Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-7725

#### **Body Style:**

Straight shape

### **Overall Length:**

1.596 inches

### **Overall Height:**

0.475 inches

### **Overall Width:**

0.124 inches

#### **Environmental Protection:**

Vibration resistant and shock resistant and humidity resistant and salt water resistant and thermal shock resistant

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end 1st contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end 1st contact grouping

## **Polarization Method:**

Contact

### **Connector Locking Method:**

Friction

### Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Back single mating end 1st contact grouping

### **Contact Surface Treatment:**

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

### **Insert Material:**

Plastic phenolic single mating end and glass fiber single mating end or plastic polyphenylene single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 1

federal specification 2nd treatment response single mating end 1st contact grouping

## **Terminal Type:**

Printed circuit single mating end 1st contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end 1st contact grouping

## Insert Material Specification:

Mil-p-46174 military specification 1st material response single mating end and mil-p-46174 military specification 2nd material response single

mating end or mil-m-14 military specification 3rd material response single mating end

## Included Contact Quantity:

15 single mating end 1st contact grouping

## Included Contact Type:

Round socket single mating end 1st contact grouping



Precious Material And Location:

Contact surfaces gold

### **Precious Material And Weight:**

0.015 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.