

View Online at <https://aerobasegroup.com/nsn/5935-01-350-0690>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, flange mount external coupling

Overall Length:

Between 1.304 inches and 1.339 inches

Overall Height:

Between 1.215 inches and 1.235 inches

Overall Width:

Between 1.215 inches and 1.235 inches

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Environmental Protection:

Corrosion resistant and vibration resistant and shock resistant and thermal shock resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.906 inches and 0.969 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.906 inches and 0.969 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

14-19 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

124.0 and 152.0 and 219.0 and 255.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

28

Thread Size:

0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Shell finish metalized

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0