NSN 5935-01-350-1215

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-350-1215

Body Style:
Straight type
Overall Length:
3.295 inches
Overall Height:
0.703 inches
Overall Width:
0.390 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
Between 0.122 inches and 0.127 inches
Distance Between Mounting Facility Centers:
2.975 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single materia

single contact grouping or qq-c-502 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24510, type ant-15f military enecification all material responses single mating and

NSN 5935-01-350-1215

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
40 single mating end single contact grouping
Included Contact Type:
Brush pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/166 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.