# NSN 5935-01-350-1217

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-350-1217 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 1.485 inches **Overall Height:** 0.448 inches **Overall Width:** 0.729 inches **Environmental Protection:** Thermal shock resistant and moisture resistant and vibration resistant and shock resistant and salt water resistant **Distance Between Mounting Facility Centers:** Between 1.260 inches and 1.270 inches **Threaded Device Type:** Coupling facility and mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end and jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches

Contact Material:

**Terminal Location:** 

Copper alloy single mating end single contact grouping

Side single mating end single contact grouping

# NSN 5935-01-350-1217

Electrical Receptacle Connector - Page 2 of 3



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-626, composition 2 federal specification single material response single mating end single contact grouping or qq-w-321, composition b federal specification single material response single mating end single contact grouping or astm b140 assn standard single material response single mating end single contact grouping

#### **Shell Material:**

Aluminum

#### **Shell Surface Treatment:**

Nickel

#### **Shell Surface Treatment Specification:**

Mil-c-26074, class 3 or 4 military specification single treatment response

# **Shell Material Specification:**

Qq-a-591, composition a380 federal specification single material response

#### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

# **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

37 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Special Features:**

Jackscrew type-female and location-right handandjackscrew type-female and location-left hand

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.037 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

# **Unit Of Measure:**

--

#### Demilitarization:

No

# Fiig:

3

# NSN 5935-01-350-1217

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.