NSN 5935-01-350-3666

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-350-3666

view Offilite at https://aerobasegroup.com/hist//3333-01-330-3000
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle shape, pcb type
Overall Length:
Between 5.070 inches and 5.130 inches
Overall Height:
0.680 inches
Overall Width:
0.620 inches
Distance Between Mounting Facility Centers:
4.900 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy 260 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2, grade f federal specification 2nd treatment response single mating end single contact grouping

NSN 5935-01-350-3666

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-613 federal specification single material response single mating end single contact grouping
Guide Design And Location:
D shape pin right-hand at 6 oclock d shape pin left-hand at 7 oclock
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, class 1a military specification single treatment response
Shell Material Specification:
Qq-a-200/8, t6 federal specification single material response
Insert Material Specification:
Mil-m-20693, type i military specification single material response single mating end
Included Contact Quantity:
135 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.135 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0