## NSN 5935-01-350-4110

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-350-4110

Body Style:
Straight shape
Overall Length:
0.778 inches
Overall Height:
0.405 inches
Overall Width:
0.173 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.088 inches and 0.096 inches
Distance Between Mounting Facility Centers:
0.565 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Plastic
Income Martanial Consideration

**Insert Material Specification:** 

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end

## NSN 5935-01-350-4110

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
C0ntact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83513 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-83513/6 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.