Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-350-5675

view Online at https://aerobasegroup.com/nsn/5935-01-350-5675
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle shape, pcb type
Overall Length:
Between 5.070 inches and 5.130 inches
Overall Height:
0.680 inches
Overall Width:
0.620 inches
Distance Between Mounting Facility Centers:
4.900 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy 260 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290,

class 2, grade f federal specification 2nd treatment response single mating end single contact grouping



Terminal	туре:
-	e mating end single contact grouping
Contact	Material Specification:
Qq-b-613	federal specification single material response single mating end single contact grouping
Guide De	esign And Location:
D shape	pin left-hand at 3 oclock d shape pin right-hand at 12 oclock
Shell Ma	terial:
Aluminum	n alloy 6061
Shell Su	face Treatment:
Chromate	
Shell Su	face Treatment Specification:
Mil-c-554	1, class 1a military specification single treatment response
Shell Ma	terial Specification:
Qq-a-200	/8, t6 federal specification single material response
Insert Ma	aterial Specification:
Mil-m-206	693, type i military specification single material response single mating end
Included	Contact Quantity:
135 single	e mating end single contact grouping
Included	Contact Type:
Flat pin si	ingle mating end single contact grouping
Precious	Material And Location:
Contact s	urfaces gold
Precious	Material And Weight:
0.135 gol	d grains, troy
Precious	Material:
Gold	
Thread S	eries Designator:
Unc	
Shelf Life	e:
N/a	
Unit Of N	leasure:
Demilitar	ization:
No	
Fiig:	
A039b0	
Mil-std (r	nilitary Standard):