NSN 5935-01-350-5679

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-350-5679 **Body Style:** Straight shape **Overall Length:** Between 2.714 inches and 2.744 inches **Overall Height:** 0.685 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.495 inches and 2.505 inches **Mating End Quantity: Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end and plastic acrylic single mating end **Criticality Code Justification:** Feat **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Metal **Shell Surface Treatment:**

Cadmium

NSN 5935-01-350-5679

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Connector kit; m24308/4-305 connector wit applicable tool

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-24308 spec.