NSN 5935-01-350-6592

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-350-6592

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, rectangular
Overall Length:
0.810 inches
Overall Height:
Between 1.062 inches and 1.092 inches
Overall Width:
Between 1.975 inches and 2.005 inches
Environmental Protection:
Thermal shock resistant and humidity resistant and vibration resistant and shock resistant and salt water resistant and corrosion resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.450 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.718 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
108 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Polarization boss
Connector Locking Method:
Jackscrew
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
32 and 56
Thread Size:
0.138 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:

Contact Surface Treatment:

Copper alloy 173 single mating end single contact grouping

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-350-6592

Electrical Receptacle Connector - Page 2 of 2



Materia	

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-46161, grade b, cl 3 military specification single material response single mating end or mil-m-24519, ty gpt-30f military specification single material response single response sing

Included Contact Quantity:

108 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.108 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.