

View Online at <https://aerobasegroup.com/nsn/5935-01-351-0481>

Body Style:

Rectangular shape

Overall Length:

0.440 inches

Overall Height:

0.770 inches

Overall Width:

0.250 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Connector Locking Method:

Friction

Features Provided:

Closed entry contact

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c or d, class 1 military specification 1st treatment response single mating end all contact groupings and qq-n-290, class 1 federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end 1st contact grouping qq-b-750 federal specification single material response single mating end 2nd contact grouping or qq-b-626 federal specification single material response single mating end 2nd contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

2 single mating end 1st contact grouping 2 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end 1st contact grouping round socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains - tray

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.