NSN 5935-01-351-0706

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-351-0706

Body Style: Rectangular shape **Overall Length:** 0.440 inches **Overall Height:** 0.530 inches **Overall Width:** 0.130 inches **Environmental Protection:** Corrosion resistant and humidity resistant **Mating End Quantity: Contact Position Arrangement Style:** 2 single mating end **Contact Removability:** Nonremovable single mating end all contact groupingsnonremovable single mating end single contact grouping **Connector Locking Method:** Friction **Features Provided:** Closed entry contact **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type ii, grade c or d, class 1 military specification single treatment response single mating end single contact grouping and qq-n-290, class 1 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-750 federal specification single material response single mating end single contact grouping or qq-b-626 federal specification single material response single mating end single contact grouping **Insert Material Specification:**

Included Contact Quantity: 2 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Mil-m-14, type sdg-f military specification single material response single mating end

Precious Material And Location:

Contact surfaces gold

NSN 5935-01-351-0706

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.