

View Online at <https://aerobasegroup.com/nsn/5935-01-351-1889>

Body Style:

Right angle type

Overall Length:

5.735 inches

Overall Height:

0.955 inches

Overall Width:

0.440 inches

Unthreaded Mounting Hole Diameter:

Between 0.141 inches and 0.142 inches

Distance Between Mounting Facility Centers:

5.450 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

End Application:

6605-01-234-5840 inertial, naviga

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 260 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613, half hard federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Chromate

Shell Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Shell Material Specification:

Qq-a-200/8, temper t6510 federal specification single material response

Included Contact Quantity:

96 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.096 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.