NSN 5935-01-351-4719

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-351-4719

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.005 inches
Overall Diameter:
0.500 inches
Distance From Mounting Shoulder To Front Face:
0.435 inches
Mounting Facility Thickness:
0.125 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Err-090 single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
0.438 inches and 0.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorocarbon single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c or d, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

NSN 5935-01-351-4719

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel comp 303
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shell Material Specification:
Astm a484 assn standard single material response or astm a582 assn standard single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.