

View Online at <https://aerobasegroup.com/nsn/5935-01-351-4724>

Body Style:

Straight shape

Overall Length:

2.700 inches

Overall Height:

0.525 inches

Overall Width:

0.095 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and shock resistant and corrosion resistant and moisture resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Connector Locking Method:

Friction

End Application:

6605-01-234-5840 inertial navigation unit

Operating Temperature Rating:

Between -65.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Included Contact Quantity:

23 single mating end single contact grouping

Included Contact Type:

Square socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.023 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.