Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-351-4729

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.062 inches
Overall Height:
Between 1.798 inches and 1.838 inches
Overall Width:
Between 1.798 inches and 1.838 inches
Environmental Protection:
Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant
Unthreaded Mounting Hole Diameter:
Between 0.147 inches and 0.152 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.392 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.392 inches
Distance From Mounting Shoulder To Front Face:
Between 0.878 inches and 0.898 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
G01 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 103.0 and 160.0 and 220.0 and 294.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Operating Tempurature Rating:
Between -55.0 degrees celsius and 200.0 degrees celsius
Thready Qty Per Inch (tpi):
18 and 10

## NSN 5935-01-351-4729

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.562 inches and 1.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorosilicone single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 1 or 2 federal specification all treatment responses
Included Contact Quantity:
92 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.092 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.