## NSN 5935-01-351-5605

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-351-5605 **Body Style:** Rectangular shape **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end and mica single mating end **Terminal Type:** Printed circuit single mating end single contact grouping **Contact Material Specification:** Qq-b-750 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty mfe military specification all material responses single mating end **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Hermaphrodite single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.014 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5935-01-351-5605

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.