

View Online at https://aerobasegroup.com/nsn/5935-01-351-7159

Thread	Class:
2a	
Thread	Direction:
Right-ha	and
Body S	tyle:
Straight	shape, external coupling
Overall	Length:
1.290 in	iches
Overall	Height:
Between	n 1.688 inches and 1.708 inches
Overall	Width:
Between	n 1.688 inches and 1.708 inches
Enviror	nmental Protection:
Moisture	e proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant
and hun	nidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant
Unthrea	aded Mounting Hole Diameter:
Betwee	n 0.142 inches and 0.157 inches
Center	To Center Distance Between Mounting Facilities Parallel To Height:
1.375 in	iches
Distanc	e Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 in	iches
Distanc	e From Mounting Shoulder To Front Face:
Betwee	n 0.785 inches and 0.790 inches
Thread	ed Device Type:
Back sh	ell
Mating	End Quantity:
1	
Contac	t Position Arrangement Style:
23-55 si	ingle mating end
Polariza	ation Method:
Keyway	or multiple keyway
Insert F	Position In Deg:
95.0 an	d 132.0 and 232.0 and 260.0 and 345.0
Shell Ty	ype:
Solid	
Connec	ctor Locking Method:
Bayone	t pin
Thread	Length:
0.219 in	iches
Thread	Size:
1.312 in	iches
Insert N	/aterial:
Plastic (epoxy single mating end



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data: 96906-ms27656 government standard Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.