Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-351-7980

## Thread Class:

2a

Thread Direction:

Right-hand and right-hand

## Body Style:

Straight shape, external coupling

### Overall Length:

1.752 inches

#### **Overall Diameter:**

1.761 inches

## Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and fuel proof and shock resistant and thermal shock resistant and vibration resistant

## Distance From Mounting Shoulder To Front Face:

1.380 inches

#### **Mounting Facility Thickness:**

0.500 inches

### **Threaded Device Type:**

Back shell and coupling facility

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

17-26 single mating end

### Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

# **Connector Locking Method:**

Externally threaded shell

# **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

# Thready Qty Per Inch (tpi):

10

#### Thread Size:

25.0 millimeters and 1.188 inches

## **Thread Pitch In Millimeters:**

1.00

#### **Terminal Location:**

Back single mating end single contact grouping



Conr	per alloy single mating end single contact grouping
	act Surface Treatment:
	single mating end single contact grouping
	n Material:
	ic epoxy single mating end
	ninal Type:
	p single mating end single contact grouping
	I Material:
Stain	less steel
Shel	I Surface Treatment:
Nicke	əl
Thre	ad Tolerance Class:
6g ex	ternal
Inclu	ded Contact Quantity:
26 si	ngle mating end single contact grouping
Busł	ning Accommodation Hole Shape:
Rour	nd w/flat
Inclu	ded Contact Type:
Rour	nd socket single mating end single contact grouping
Prec	ious Material And Location:
Cont	act surfaces gold
Prec	ious Material And Weight:
0.026	6 gold grains, troy
Prec	ious Material:
Gold	
Thre	ad Series Designator:
lso m	n and special acme
Shel	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	