NSN 5935-01-351-7980

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-351-7980 **Thread Class:** 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.752 inches **Overall Diameter:** 1.761 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and fuel proof and shock resistant and thermal shock resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 1.380 inches **Mounting Facility Thickness:** 0.500 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 17-26 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 10 **Thread Size:**

1.00

Terminal Location:

25.0 millimeters and 1.188 inches

Thread Pitch In Millimeters:

Back single mating end single contact grouping

NSN 5935-01-351-7980

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Nickel
Thread Tolerance Class:
6g external
Included Contact Quantity:
26 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Iso m and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0