

View Online at <https://aerobasegroup.com/nsn/5935-01-352-0956>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

31.5 millimeters

Overall Height:

39.7 millimeters

Overall Width:

39.7 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 29.36 millimeters and 31.75 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 29.36 millimeters and 31.75 millimeters

Distance From Mounting Shoulder To Front Face:

20.1 millimeters

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

10

Thread Size:

21.0 millimeters and 1.375 inches

Thread Pitch In Millimeters:

1.00

Insert Material:

Plastic epoxy single mating end

Shell Material:

Steel

Shell Surface Treatment:

Nickel

Thread Tolerance Class:

6g external

Thread Series Designator:

Iso m and special acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0