

View Online at <https://aerobasegroup.com/nsn/5935-01-353-1410>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Angle shape, pcb, external coupling

Overall Length:

Between 0.490 inches and 0.530 inches

Overall Height:

0.615 inches

Overall Width:

0.250 inches

Environmental Protection:

Corrosion resistant and vibration resistant and shock resistant and thermal shock resistant and salt water resistant

Distance From Mounting Shoulder To Front Face:

0.230 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36

Thread Size:

0.190 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 173 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1 or 2, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Gold and nickel

Shell Surface Treatment Specification:

Mil-g-45204, type 2, grade c military specification 1st treatment response and qq-n-290 federal specification 2nd treatment response

Shell Material Specification:

Astm-a582 assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end and l-p-403 federal specification 2nd material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.