NSN 5935-01-353-5841

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5035-01-353-58/1

view Online at https://aerobasegroup.com/hsn/5935-01-353-5641
Body Style:
Straight shape
Overall Length:
1.340 inches
Overall Height:
0.600 inches
Overall Width:
0.234 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
2.0 single mating end all contact groupings2.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -67.0 degrees fahrenheit and 221.0 degrees fahrenheit
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federa
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Printed circuit single mating end single contact grouping
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:

Precious Material And Location: Contact surfaces gold

Square socket single mating end single contact grouping

Precious Material And Weight:

0.024 gold grains, troy

NSN 5935-01-353-5841

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.