## NSN 5935-01-354-4707

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-354-4707

**Body Style:** Straight shape **Overall Length:** 0.606 inches **Overall Height:** 0.395 inches **Overall Width:** 0.240 inches **Environmental Protection:** Thermal shock resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -65.0 degrees celsius and 105.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, cl 0 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-750 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 

12 single mating end single contact grouping

## **Included Contact Type:**

Leaf spring single mating end single contact grouping

## NSN 5935-01-354-4707

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.012 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.