--

Electrical Connector Retaining Plate - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-354-5345

34         Sigh-hand         Coral Length:         1.65 incles         Conter Conter Distance Between Mounting Facilities Parallel To Length:         1.260 incles         Conter To Center Distance Between Mounting Facilities Parallel To Width:         1.260 incles         Overall Height:         1.260 incles and 0.166 incles         Overall Height:         1.865 incles         Overall Height:         1.865 incles         Mounting Facilities Parallel To Width:         1.865 incles         Overall Height:         1.865 incles         Mounting Facilities Parallel To Width:         1.875 incles         1.885 incles         0.112 incles         3.986 inclustor incles         0.128 inclustor incles         0.128 inclustor incles         Mainer alloy         Subian Cattor in one side         Subian Cattor in one side         Subian Cattor in one side         Subian Cattor in one side </th <th>Thread Class:</th> <th></th>	Thread Class:	
Righthand         Overal Longht:         1.665 inchos         Conter T Conter Distance Between Mounting Facilities Parallel To Length:         1.250 inchos         Conter To Conter Distance Between Mounting Facilities Parallel To Width:         1.250 inchos         Conter I Ostance Between Mounting Facilities Parallel To Width:         1.250 inchos         Overall Högh:         Between 0.106 inches and 0.166 inches         Overall Width:         1.665 inches         Mounting Facility Type And Quantity:         4 dinch nut         Thread Yup Par Inch (pi):         4 dinch nut         Special Factures:         0.4011 Factures:         0.4021 Fotumes:         0.4021 Fotumes:         0.4031 Fotumes:         0.4031 Fotumes:         0.4041 Fotumes:         0.4051 Fotumes:         0.4051 Fotumes:         0.4061 Fotumes:         0.4071 Fotumes:         0.4081 Fotumes:	3b	
Overall Length:           1.685 inches           Center To Center Distance Between Mounting Facilities Parallel To Length:           1.200 inches           Center To Center Distance Between Mounting Facilities Parallel To Width:           1.200 inches           Orderil Height:           Between 0.106 inches and 0.166 inches           Overall Width:           1.665 inches           Mounting Facility Type And Quantity:           1.665 inches           Mounting Facility Pointed (pi):           1.012 inches           Mounting Bacility Pointed (pi):           0.566 in Cutoux on one side           Material:           Aurinum allay           Munium allay           Surface Treatment:           Chormet           Sulva Designator:           Quare shape           Sulva	Thread Direction:	
1.865 indes           Center Conter Distance Between Mounting Facilities Parallel To Length:           1.250 indes           Center To Center Distance Between Mounting Facilities Parallel To Width:           1.250 indes           Conter To Center Distance Between Mounting Facilities Parallel To Width:           1.250 indes           Overall Weight:           Reader Distance Between Mounting Facilities Parallel To Width:           Deveal Weith:           1.365 indes           Mounting Facility Type And Quantity:           1.466 indu           Thready Dype Inch (pt):           1.01           Distance           0.121 indes           Distance           0.122 indes           Distance           Distance           0.122 indes           Distance           Distance           0.122 indes           Distance	Right-hand	
Cherr O Center Distance Between Mounting Facilities Parallel To Undeth:         1.250 inches         Cherrer Distance Between Mounting Facilities Parallel To Width:         1.250 inches         Overall Height:         Between 0.106 inches and 0.166 inches         Overall Width:         1.665 inches         Mounting Facility Type And Quantity:         4 clinch nut         Thready Dy Pr Inch (ptp):         40         Thready Dy Pr Inch (ptp):         1012 Inches         1022 Inches         Aureital         Starte Teatement:         Aureital         Starte Teatement:         Starte Teatement: </td <td>Overall Length:</td> <td></td>	Overall Length:	
1250 Inches         Center To Center Distance Between Mounting Facilities Parallel To Width:         1.250 Inches         Overall Height:         Edween 0.106 Inches and 0.166 Inches         Overall Width:         1.650 Inches         Verall Height:         1.665 Inches         Mounting Facility Type And Quantity:         4 clinch nut         Thready Gyper Inch (fpi):         40         1.121 Inches         Special Factors:         0.112 Inches         Special Factors:         0.122 Inches         Auminum alloy         Material:         Auminum alloy         Surface Treatment:         Chromate         Stylface Treatment: <td>1.665 inches</td> <td></td>	1.665 inches	
Cherer Conter Distance Between Mounting Facilities Parallel To Width: 1.250 Inches Overall Width: Between 0.106 Inches and 0.166 Inches Overall Width: 1.665 Inches Mounting Facility Type And Quantity: 4. Gloch nut Thready Gyper Inch (pi): 4. Gloch nut Thready Gyper Inch (pi): 4. Gloch nut Thread Size: 0.112 Inches Special Features: 0.112 Inches Special Features: 1.121 Inches Special Features: 1.121 Inches Special Features: 1.121 Inches 1.121	Center To Center Distance Between Mounting Facilities Parallel To Length:	
1.250 inches         Cverall Height:         Betwen0.106 inches and 0.166 inches         Overall Width:         1.665 inches         Mounting Facility Type And Quantity:         1.665 inches         Mounting Facility Type And Quantity:         1.665 inches         Thready Qty Per Inch (tpi):         40         Threads Zta:         0.112 Inches         Special Features:         0.122 Inches         Special Features:         0.968 in. Cutout on one side         Material:         Aluminum alloy         Surface Treatment:         Quantic Argument and	1.250 inches	
Nerall Height:Between 0.106 inches and 0.166 inchesGiveen 0.106 inches and 0.166 inchesCheel Widht:1.686 inchesMonting Facility Type And Quantity:4 clinch nutThready Chy Per Inch (tp):40Thready Chy Per Inch (tp):40Special Factures:0.1012 inchesSpecial Factures:0.968 in. Cutout on one sideMaterial:Auminum alloyAuminum alloySurface Treatment:ChromateSylare StapeSylare StapeSurface Treatment:ChromateStape Stape Stap	Center To Center Distance Between Mounting Facilities Parallel To Width:	
Beween 0.106 inches and 0.166 inches         Cycrall Widt:         1.65 inches         Mounting Facility Type And Quantity:         4 dinch nut         Thready Qiv Per Inch (tp):         40         Thread Size:         0.112 Inches         Special Festures:         0.308 in. Cutout one side         Material:         Atuminum alloy         Material:         Special Festures:         Outminum alloy         Surface Treatment:         Syle Designator:         Square Shape         Syle Designator:         Square Shape         Straface Treatment:         Chromate         Straface Treatment:         Straface Treatment:         Straface Studys specification (includes engineering type bulletins, brochures, etc., that reflect specification specification treatment:         Straface Studys specification specification         Straface Studys specification speci	1.250 inches	
Noreal Width:         1.665 inches         Mounting Facility Type And Quantity:         4 clinch nut         Thready Oty Per Inch (tpi):         40         Thread Size:         0.112 inches         Boelal Features:         0.968 in. Cutout on one side         Material:         Aluminum alloy         Autrinum alloy         Stread Features:         Otype Signator:         Autrinum alloy         Stread Features:         Otype Signator:         Stread Features:         Stread Features:         Chromate         Stread Features:         Stread Features:         Stread Features:         Stread Features:         Stread Features:         Chromate         Stread Features:	Overall Height:	
1.685 Inclus         Mounting Facility Type And Quantity:         4 clinch nut         Thready Qy Per Inch (tpi):         40         Thread Yu Per Inch (tpi):         40         Thread Size:         0.112 Inches         Special Features:         0.305 In: Cutout on one side         Material:         Aluminum alloy         Surface Treatment:         Chromate         Surface Treatment:         Chromate         Surface Treatment:         Chromate         Surface Treatment:         Chromate         Stadya Shape         Stadya Shape         Surface Treatment:         Chromate         Stadya Shape         Stadya Shape         Stadya Shape         Stadya Shape         Stadya Shape Sh	Between 0.106 inches and 0.166 inches	
Alonding Facility Type And Quantity:         4 kinch nut         Thready Qiv Per Inch (tpi):         40         Thread Size:         0.112 linches         Byzeial Features:         0.308 kin Cutoto one side         Material:         Autorial:         Autorial:         Autorial:         Autorial:         Autorial:         Autorial:         Autorial:         Autorial:         Autorial:         Style Designator:         Chromate         Style Designator:         Chromate         Stardae Teaturent:         Chromate         Teaturent:         Chromate         Stardae Te	Overall Width:	
4 clinch nut         Thready Qty Per Inch (tpi):         40         Thread Size:         0.112 inches         Special Features:         0.968 in. Cutout one side         Material:         Aluminum alloy         Material:         Aluminum alloy         Surface Treatment:         Chromate         Style Designator:         Square shape         Chromate         Test Data Document:         Chromate         Test Data Document:         Chromate         Style Designator:         Square shape         Chromate         Test Data Document:         Chromate         Style Designator:         Style Designator:         Style Designator:         Style Designator:         Chromate         Test Data Document:         Chromate         Thread Style Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification or eretainering type data on certainering type data on certainerine certainering type data on certainering typ	1.665 inches	
Hready Quy Per Inch (tpi):         40         Hread Size:         0.112 inches         Special Features:         0.968 in. Cutout on one side         Maerial:         Numium alloy         Material:         Outmout on going         Sylace Teatument:         Chromate         Stylace Treatment:         Outmout on Comment on C	Mounting Facility Type And Quantity:	
40 Thread Size: Control of the set of the se	4 clinch nut	
Thread Size:0.112 inchesSpecial Features:0.608 in. Cutout on one sideMaterial:Aluminum alloyMaterial:Aluminum alloySuface Treatment:ChromateStyle Designator:Sturface Treatment:ChromateSturface Treatment:ChromateSturface Treatment:Sturface Treatment:ChromateSturface Treatment:ChromateSturface Treatment:ChromateSturface Treatment:ChromateTotal Document:ChromateSturface Treatment:ChromateSturface Treatment:ChromateSturface Treatment:ChromateSturface Treatment:ChromateSturface Treatment:ChromateSturface Treatment:Sturface Treatment:Sturface Treatment:Sturface Treatment:Sturface Scolingenting industry directories, and similar trade publications, reflecting general type data on certainerSturface Sturface SturfaceSturface Treatment:Sturface Sturface Scolingator:Sturface Sturface SturfaceSturface Sturface SturfaceSturface Sturface SturfaceSturface Sturface Sturface SturfaceSturface Sturface SturfaceSturface Sturface Sturface SturfaceSturface Sturface Sturface Sturface SturfaceSturface Sturface Stu	Thready Qty Per Inch (tpi):	
0.12 indes Special Features: 0.698 in Cutout on one side Material: Aluminum alloy Material: Aluminum alloy Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Chromate Syle Designator: Square shape Chromate State Treatment: Chromate State Designation: State Designation: Chromate State Designa	40	
Special Features:0.968 in. Cutout on one sideMaterial:Aluminum alloyMaterial:Aluminum alloySurface Treatment:ChromateStyle Designator:Square shapeChromateStraface Treatment:ChromateStraface Treatment:Straface Treatment:Straface Treatment:Straface Treatment:Straface Treatment:Straface Treatment:Straface Treatment:ChromateStraface Treatment:Straface Treatment: <t< td=""><td>Thread Size:</td><td></td></t<>	Thread Size:	
0.968 in. Cutout on one sideMaterial:Aluminum alloyMaterial:Aluminum alloySurface Treatment:ChromateStyle Designator:Square shapeChromateStraface Treatment:ChromateStraface Treatment:ChromateStraface Treatment:ChromateStraface Treatment:ChromateStraface Treatment:ChromateChromateTest Data Document:R1349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationrimati, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainrinorumental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).Thread Series Designator:UncSpecification Data:R1349-mil-c-85049/95 government specificationShelf Life:Na	0.112 inches	
Material:Aluminum alloyMaterial:Aluminum alloySurface Treatment:ChormateStyle Designator:Square shapeChromateSurface Treatment:ChormateSurface Treatment:ChormateSurface Treatment:ChormateDesignator:ChormateDesignator:ChormateDesignator:ChormateThe Data Document:Stl49-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationrinart: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainenvironmental and performance requirements and test conditions that are shown as "typical", "average", "**, etc.).Thread Series Designator:UncSpecification Data:Stl49-mil-c-85049/sg government specificationShelf Life:Na	Special Features:	
Aluminum alloy         Material:         Aluminum alloy         Surface Treatment:         Chromate         Surface Treatment:         Square shape         Surface Treatment:         Chromate         Surface Treatment:         Chromate         Surface Treatment:         Chromate         Surface Treatment:         Chromate         Test Data Document:         S1349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain         romate, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         romate, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         unc         Specification Data:         Stade-mil-c-85049/sp government specification         Sheft Life:         Na	0.968 in. Cutout on one side	
Material:Aluminum alloySurface Treatment:ChromateShyle Designator:Square shapeSurface Treatment:ChromateChromateSurface Treatment:ChromateStarface Treatment:ChromateSurface Treatment:ChromateTest Data Document:Stafds-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).Thread Series Designator:UncSpecification Data:Stafds-mil-c-85049/sg government specificationSheff Life:Na	Material:	
Aluminum alloy Surface Treatment: Chromate Chromate Style Designator: Square shape Surface Treatment: Chromate	Aluminum alloy	
Surface Treatment:ChromateStyle Designator:Square shapeSurface Treatment:ChromateChromate19349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationchromate and performance requirements and test conditions that are shown as "typical", "average", "", etc.).Thread Series Designator:UncSpecification Data:81349-mil-c-85049/95 government specificationB1349-mil-c-85049/95 government specificationMide Liffe:N/a	Material:	
Chromate Style Designator: Square shape Surface Treatment: Chromate Chromate Chromate Test Data Document: S1349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (romate, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc Specification Data: S1349-mil-c-85049/95 government specification	Aluminum alloy	
Style Designator:Square shapeSurface Treatment:ChromateTest Data Document:81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).Thread Series Designator:UncSpecification Data:81349-mil-c-85049/95 government specification81349-mil-c-85049/95 government specificationN/a	Surface Treatment:	
Square shape Surface Treatment: Chromate Test Data Document: 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc Specification Data: 81349-mil-c-85049/95 government specification Shelf Life: N/a	Chromate	
Surface Treatment: Chromate Test Data Document: 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc Specification Data: 81349-mil-c-85049/95 government specification Shelf Life: N/a	Style Designator:	
Chromate Test Data Document: 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc Specification Data: 81349-mil-c-85049/95 government specification Shelf Life: N/a	Square shape	
Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification         format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:         Unc         Specification Data:         81349-mil-c-85049/95 government specification         Shelf Life:         N/a	Surface Treatment:	
81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc Specification Data: 81349-mil-c-85049/95 government specification Shelf Life: N/a	Chromate	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc Specification Data: 81349-mil-c-85049/95 government specification Shelf Life: N/a	Test Data Document:	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unc Specification Data: 81349-mil-c-85049/95 government specification Shelf Life: N/a	81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	วท
Thread Series Designator:   Unc   Specification Data:   81349-mil-c-85049/95 government specification   Shelf Life:   N/a	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Unc Specification Data: 81349-mil-c-85049/95 government specification Shelf Life: N/a	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:         81349-mil-c-85049/95 government specification         Shelf Life:         N/a	Thread Series Designator:	
81349-mil-c-85049/95 government specification Shelf Life: N/a	Unc	
Shelf Life: N/a	Specification Data:	
N/a	81349-mil-c-85049/95 government specification	
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	



Demilitarization:

No

Fiig:

A10100