

View Online at <https://aerobasegroup.com/nsn/5935-01-354-6099>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

0.875 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and shock resistant and thermal shock resistant and moisture resistant

**Cable Entrance Diameter:**

0.141 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Smc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.5 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Compression nut

**End Application:**

5895-01-168-7286 interrogator set

**Width Across Flats:**

0.281 inches

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 165.0 degrees celsius

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-c-45204, type 1, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl 4 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold

**Shell Material Specification:**

Qq-b-626 federal specification single material response

**Insert Material Specification:**

Astm d 1710, type 1, grade 1 assn standard single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Body and contact surfaces gold

**Precious Material And Weight:**

0.101 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-45204 spec.