NSN 5935-01-355-2431

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-355-2431

View Online at https://aerobasegroup.com/nsn/5935-01-355-2431
Body Style:
Straight type
Overall Length:
6.295 inches
Overall Height:
0.670 inches
Overall Width:
0.390 inches
Unthreaded Mounting Hole Diameter:
Between 0.124 inches and 0.130 inches
Distance Between Mounting Facility Centers:
5.975 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass fiber single mating end and plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-p-46161, grade b, cl 15 military specification all material responses single mating end
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Brush socket single mating end single contact grouping
Precious Material And Location:

Contact surfaces gold

NSN 5935-01-355-2431

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - unthreaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-p-46161 spec.