Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-355-2431

| Body Style: |
|---------------------------------------------------------------------------------------------|
| Straight type |
| Overall Length: |
| 6.295 inches |
| Overall Height: |
| 0.670 inches |
| Overall Width: |
| 0.390 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.124 inches and 0.130 inches |
| Distance Between Mounting Facility Centers: |
| 5.975 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Glass fiber single mating end and plastic single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Insert Material Specification: |
| Mil-p-46161, grade b, cl 15 military specification all material responses single mating end |
| Included Contact Quantity: |
| 100 single mating end single contact grouping |
| Included Contact Type: |
| Brush socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |



Precious Material And Weight: 0.100 gold grains, troy **Precious Material:** Gold Supplementary Features: Mounting method - unthreaded hole Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-p-46161 spec.