Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-355-7043

### **Body Style:**

Straight shape

#### **Overall Length:**

5.560 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

#### Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

Connector Locking Method:

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Insert Material:**

Plastic polyester glass filled single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification

2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Printed circuit single mating end single contact grouping

### **Guide Design And Location:**

D shape pin left-hand top at 12 oclock and d shape pin right-hand top at 12 oclock

#### **Included Contact Quantity:**

123 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.123 gold grains, troy

### Precious Material:

Gold

#### Shelf Life:

N/a

#### Unit Of Measure:



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.