## NSN 5935-01-355-7045

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-355-7045 **Body Style:** Straight shape **Overall Length:** 5.560 inches **Unthreaded Mounting Hole Diameter:** Between 0.140 inches and 0.146 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 3 rows of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyester glass filled single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Printed circuit single mating end single contact grouping **Included Contact Quantity:** 123 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.123 gold grains, troy **Precious Material:** Gold

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5935-01-355-7045

Electrical Receptacle Connector - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.