NSN 5935-01-356-4157

Thread Class: 2a and 2b

Right-hand

Thread Direction:

Terminal Type:

Crimp single mating end single contact grouping

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-356-4157

Body Style:
Straight shape, internal coupling
Overall Length:
1.370 inches
Overall Diameter:
1.682 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
18.0 and 149.0 and 192.0 and 259.0
Shell Type:
Shell Type: Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Internally threaded coupling ring
Solid Connector Locking Method: Internally threaded coupling ring Thread Length:
Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches
Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating:
Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius
Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius Thread Size:
Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius Thread Size: 1.312 inches and 1.437 inches
Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius Thread Size: 1.312 inches and 1.437 inches Terminal Location:
Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius Thread Size: 1.312 inches and 1.437 inches Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius Thread Size: 1.312 inches and 1.437 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius Thread Size: 1.312 inches and 1.437 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Internally threaded coupling ring Thread Length: 0.290 inches Operating Tempurature Rating: Between -65.0 degrees celsius and 200.0 degrees celsius Thread Size: 1.312 inches and 1.437 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:

NSN 5935-01-356-4157Electrical Plug Connector - Page 2 of 2



Stainless steel Shell Surface Treatment: Passivate Included Contact Quantity: 55 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life: N/a	
Passivate Included Contact Quantity: 55 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Included Contact Quantity: 55 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Precious Material And Location: Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Contact surfaces gold Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Precious Material: Gold Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Test Data Document: 81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	ition
Thread Series Designator: Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Unef Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
Specification Data: 81349-mil-c-83723/95 government specification Shelf Life:	
81349-mil-c-83723/95 government specification Shelf Life:	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	