NSN 5935-01-356-4183

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-356-4183 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.500 inches **Overall Height:** 1.437 inches **Overall Width:** 1.437 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-41 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 95.0 and 145.0 and 220.0 and 255.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell

Thread Length:

0.290 inches and 0.228 inches

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

NSN 5935-01-356-4183

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18
Thread Size:
1.188 inches and 1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
41 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.041 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0