NSN 5935-01-356-9264

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-356-9264 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 3.900 inches **Overall Height:** 0.665 inches **Overall Width:** 0.350 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 3.200 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 3 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

NSN 5935-01-356-9264

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-46174, cl 40, grade e military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

92 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-female and location-right handandjackscrew type-male and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.092 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.