

View Online at <https://aerobasegroup.com/nsn/5935-01-357-1043>

**Body Style:**

Straight shape

**Overall Length:**

3.750 inches

**Overall Height:**

0.629 inches

**Overall Width:**

0.585 inches

**Environmental Protection:**

Humidity resistant and corrosion resistant and salt spray proof and vibration resistant and shock resistant and moisture resistant

**Distance Between Mounting Facility Centers:**

3.450 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

4 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14f, type sgd-f military specification 1st material response single mating end or mil-m-24519, type gst-40f military specification 2nd material response single mating end

**Included Contact Quantity:**

120 single mating end single contact grouping

**Included Contact Type:**

Square socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.120 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.