NSN 5935-01-357-1044

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-357-1044

Body Style:
Straight shape
Overall Length:
1.435 inches
Overall Height:
0.616 inches
Overall Width:
0.351 inches
Unthreaded Mounting Hole Diameter:
Between 0.088 inches and 0.094 inches
Distance Between Mounting Facility Centers:
Between 1.210 inches and 1.220 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
51 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
4931-01-318-5730 test set, fire control system
Features Provided:
Rfi shielding
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyester glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:

Onen material.

Aluminum alloy 6061

NSN 5935-01-357-1044

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification single treatment response

Shell Material Specification:

Qq-a-200/8, temper t6 federal specification single material response

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Shelf Life: N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.