Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-357-2368

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Height:

1.170 inches

Overall Diameter:

0.625 inches

Environmental Protection:

Corrosion resistant

Cable Entrance Diameter:

Between 0.065 inches and 0.069 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy 360 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military

specification 2nd treatment response single mating end single contact grouping



NSN 5935-01-357-2368

Electrical Plug Connector - Page 2 of 2



Terminal Type: Crimp single mating end single contact grouping **Contact Material Specification:** Qq-b-626, half hard federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy 360 **Shell Surface Treatment:** Silver and copper **Shell Surface Treatment Specification:** Qq-s-365 federal specification 2nd treatment response and mil-c-14550 military specification 2nd treatment response **Shell Material Specification:** Qq-b-626, half hard federal specification single material response **Insert Material Specification:** Astm d1710 assn standard single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.