NSN 5935-01-357-3296

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5035-01-357-3206

view Online at https://aerobasegroup.com/hsn/5955-01-557-5296
Body Style:
Straight type
Overall Length:
3.895 inches
Overall Height:
0.670 inches
Overall Width:
0.490 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.575 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact
grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end
Terminal Type:
Printed circuit single mating end single contact grouping

Printed circuit single mating end single contact grouping

Included Contact Quantity:

104 single mating end single contact grouping

Included Contact Type:

Brush socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.104 gold grains, troy

NSN 5935-01-357-3296

Electrical Receptacle Connector - Page 2 of 2



Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/169 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0