

View Online at <https://aerobasegroup.com/nsn/5935-01-357-4196>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.500 inches

Overall Height:

Between 2.219 inches and 2.281 inches

Overall Width:

Between 2.219 inches and 2.281 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Unthreaded Mounting Hole Diameter:

Between 0.168 inches and 0.183 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.750 inches

Distance From Mounting Shoulder To Front Face:

Between 0.875 inches and 0.906 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

32-17 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

135.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18

Thread Size:

2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Rubber silicone class q single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.020 silver grains, troy

Precious Material:

Silver

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

96906-ms3450 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N

Fig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.