## NSN 5935-01-357-5575

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-357-5575 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape, pcb type **Overall Length:** 1.475 inches **Overall Height:** 0.405 inches **Overall Width:** 0.725 inches **Environmental Protection:** Shock resistant and thermal shock resistant and vibration resistant and moisture resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.070 inches and 0.075 inches **Distance Between Mounting Facility Centers:** 1.265 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** 

Side single mating end single contact grouping Contact Material:

Copper alloy single mating end single contact grouping

## NSN 5935-01-357-5575

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester single mating end
Terminal Type:
Printed circuit single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Nickel
Shell Material Specification:
Qq-a-200/8 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519 military specification 2nd material response
single mating end
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.