

View Online at <https://aerobasegroup.com/nsn/5935-01-358-0843>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.690 inches

Overall Height:

0.700 inches

Overall Width:

0.190 inches

Distance Between Mounting Facility Centers:

0.468 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

5 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.5 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Special features dip solder terminal length 0.150 in. Min to 0.198 in. Max; jackscrew type-female and location-right handandjackscrew type-male and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0