# NSN 5935-01-358-1042

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-358-1042

#### **Body Style:**

Angle, shape, internal coupling

## **Overall Length:**

1.350 inches

# **Overall Height:**

1.090 inches

#### **Overall Diameter:**

0.500 inches

#### **Environmental Protection:**

Corrosion resistant and fungus resistant

## Cable Entrance Diameter:

0.216 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Bnc single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

#### Shell Type:

Solid

## **Connector Locking Method:**

Bayonet slot

# **Connector Cable Strain Relief Method:**

Compression nut

#### **Terminal Location:**

Side single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# Shell Material:

Copper alloy 360

## **Shell Material Specification:**

Qq-b-626 federal specification single material response

# NSN 5935-01-358-1042

Electrical Plug Connector - Page 2 of 2



**Included Contact Quantity:** 

1 single mating end single contact grouping

## Included Contact Type:

Coaxial socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.005 gold grains, troy

# **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.