

View Online at <https://aerobasegroup.com/nsn/5935-01-358-1304>

**Body Style:**

Rectangular shape, insulation

**Overall Length:**

1.680 inches

**Overall Height:**

0.640 inches

**Overall Width:**

0.240 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Connector Cable Strain Relief Method:**

Bracket

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Insulation piercing single mating end single contact grouping

**Included Contact Quantity:**

30 single mating end single contact grouping

**Included Contact Type:**

Square socket single mating end single contact grouping

**Special Features:**

Polarization, center bump

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.030 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.