## NSN 5935-01-358-1911

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-358-1911

**Body Style:** 

Right angle type

**Overall Length:** 

8.900 inches

**Overall Width:** 

Between 0.165 inches and 0.185 inches

**Body Height:** 

Between 0.170 inches and 0.200 inches

**Mating End Quantity:** 

1

### **Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

### **Connector Locking Method:**

Friction

### **Terminal Location:**

Side single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic polyphenylene single mating end and glass single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-p-46174 military specification single material response single mating end

## **Included Contact Quantity:**

89 single mating end single contact grouping

## **Included Contact Type:**

Leaf spring single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.089 gold grains, troy

# NSN 5935-01-358-1911

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.