## NSN 5935-01-358-1915

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-358-1915

**Body Style:** Right angle type **Overall Length:** 7.528 inches Overall Width: 0.450 inches **Body Height:** 0.238 inches **Unthreaded Mounting Hole Diameter:** Between 0.093 inches and 0.098 inches **Distance Between Mounting Facility Centers:** Between 7.248 inches and 7.268 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Printed circuit single mating end single contact grouping **Contact Material Specification:** 

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-p-46174 military specification single material response single mating end

### **Included Contact Quantity:**

140 single mating end single contact grouping

#### **Included Contact Type:**

Leaf spring single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

# NSN 5935-01-358-1915

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.140 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.