NSN 5935-01-358-3972

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5035-01-358-3072

view Online at https://aerobasegroup.com/hsh/5935-01-356-3972
Body Style:
Straight shape
Overall Length:
5.630 inches
Overall Height:
0.777 inches
Overall Width:
0.540 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and moisture resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
Between 0.205 inches and 0.213 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-b-613 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

NSN 5935-01-358-3972

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, cl 3 military specification single treatment response
Shell Material Specification:
Qq-a-200/8 federal specification single material response
Insert Material Specification:
Mil-m-20693, type 1 military specification single material response single mating end
Included Contact Quantity:
126 single mating end single contact grouping
Included Contact Type:
Square pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.126 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Λ 030b0