Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-358-3974

Body Style:

Straight type

Overall Length:

3.295 inches

Overall Height:

0.670 inches

Overall Width:

0.590 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

0.122 inches

Distance Between Mounting Facility Centers:

2.975 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

4 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact

grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Terminal Type:

Printed circuit single mating end single contact grouping

Included Contact Quantity:

80 single mating end single contact grouping

Included Contact Type:

Brush socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.080 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



Precious Material:

Gold

Test Data Document:

81346-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/169 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A039b0