Electrical Connector Backshell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-358-4334

New Online at https://aerobasegroup.com/nsi//3535-01-350-4354
Thread Direction:
Right-hand
Seal Material:
Rubber, silicone base
Furnished Items:
Rfi ring
Overall Length:
6.530 inches
Overall Height:
Between 1.735 inches and 1.765 inches
Overall Width:
1.470 inches
Cable Opening Diameter:
Between 0.501 inches and 0.625 inches
Thread Length:
7.11 millimeters
Cable Opening Quantity:
1
Seal Type:
Grommet and preformed packing
Size Designation:
Size Designation: 25
-
25
25 Mounting Facility Type And Quantity:
25 Mounting Facility Type And Quantity: 1 threaded coupling
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size:
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters Thread Pitch In Millimeters:
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class:
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6g internal
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6g internal Material:
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6g internal Material: Aluminum alloy
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6g internal Material: Aluminum alloy Surface Treatment:
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6g internal Material: Aluminum alloy Surface Treatment: Cadmium and chromate and nickel
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 37.0 millimeters 37.0 millimeters 37.0 millimeters 1.00 Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6g internal 6g internal Material: Aluminum alloy Surface Treatment: Cadmium and chromate and nickel Style Designator:
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Coupling Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 1.00 Thread Tolerance Class: 6g internal Material: Aluminum alloy Surface Treatment: Cadmium and chromate and nickel Style Designator: Straight type w/cable clamp
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Coupling Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 1.00 Thread Tolerance Class: 6g internal Material: Aluminum alloy Surface Treatment: Cadmium and chromate and nickel Style Designator: Straight type w/cable clamp Surface Treatment:
25 Mounting Facility Type And Quantity: 1 threaded coupling Thread Coupling Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 1.00 Thread Tolerance Class: 6g internal Material: Aluminum alloy Surface Treatment: Cadmium and chromate and nickel Straight type w/cable clamp Surface Treatment: Cadmium and chromate and nickel, electroless

N/a

Electrical Connector Backshell - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A10100